



## Coil Specification (at 20 °C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ( $\Omega \pm 8\%$ )	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
BPC-DM	3	150.0	20	Abt. 0.45	75% Maximum	10% Minimum	130%
	5	90.00	55				
	6	75.00	80				
	9	50.00	180				
	12	37.50	320				
	24	18.75	1280				
	48	9.37	5120				

## Ordering Information

<b>BPC</b>	-	<b>SS</b>	-	<b>1</b>		<b>12</b>		<b>D</b>		<b>M</b>
<b>Contact Form: M:One form A</b>										
<b>Coil Type: D:Standard DC Coil</b>										
<b>Coil Voltage: 03:3V, 05:5V,06:6V,09:9V 12:12V,24:24V,48:48V</b>										
<b>Number of Pole: 1:One Pole</b>										
<b>Type of Sealing: SS:Plastic Sealed Type</b>										
<b>Type: BPC</b>										

## Classification

Model	<b>BPC</b>
Coil Sensitivity	Standard DC Coil 1A
Plastic Sealed Type	BPC-SS-1□□DM

## Dimension

