

**Features**

- Miniature;
- Contact load capacity up to 30A;
- Terminal types as inserting;
- Suitable for automobile system and automobile auxiliary etc.

**Ordering Information 订货说明**

<b>WM726</b>	<b>- 12</b>	<b>- A</b>
<b>1</b>	<b>2</b>	<b>3</b>

1 Part number 继电器型号: WM726 (with Insulation Bracket 带塑料安装背)

2 Coil rated Voltage(VDC)线圈额定电压: 6: 6V; 12: 12V; 24: 24V

3 Contact Form 触点形式: A: 1A

**Contact Data 触点参数**

Contact Form 触点形式	1A (SPSTNO)
Contact Material 触点材料	Ag Alloy
Contact Rating (resistive) 触点负载 (阻性)	1A 30A/14VDC
Max. Switching Voltage 最大切换电压	75VDC
Max. Switching Current 最大切换电流	30A
Max. Switching Power 最大切换功率	420W
Contact Resistance or Voltage drop 接触电阻或接触压降	≤100mV (at 30A)
Electrical Life 电气寿命	1×10 <sup>5</sup> 次
Mechanical Life 机械寿命	1×10 <sup>7</sup> 次

**Coil Parameter 线圈参数**

Dash numbers 规格	Coil voltage 线圈电压(VDC)		Coil resistance 线圈电阻 Ω±10%	Pickup voltage VDC(Max.) 最大起动作电压	Release voltage VDC(Min.) 最小释放电压	Coil power 线圈功率	Operate Time 起动时间	Release Time 释放时间
	Rated 额定	Max. 最大						
6V	6V	7.8V	25	4.2V	0.6V	1.44W	≤7 ms	≤5 ms
12V	12V	15.6V	100	8.4V	1.2V			
24V	24V	31.2V	400	16.8V	2.4V			

**Operation condition 工作条件**

Insulation Resistance 绝缘电阻		100MΩ Min. (at 500VDC)
Dielectric Strength 介质耐压	Between Contacts	50Hz 500VAC / 1 minute
	Between Coil and Contacts	50Hz 750VAC / 1 minute
Shock resistance 抗冲击		147m/s <sup>2</sup> 11ms
Vibration resistance 抗震		10~40Hz double amplitude 1.5mm
Terminals strength 引出端强度		100N
Solderability 可焊性		235°C±2°C 10±0.5s
Ambient Temperature 环境温度		-40°C ~ +85°C
Relative Humidity 相对湿度		85% (at 40°C)
Weight 重量(Approx.)		33g

**Layout (Bottom views, Unit: mm)外形尺寸、接线图 (底视图)**
