



Auto LED Flasher WM FLL301

L×W×H(mm): 30.5×30.5×30(+14)/
30.5×30.5×39(+14)



Features

- Suitable for flasher light during car turning;
- High sensitive and stable electronic timing;
- Wide operating voltage, temperature range and long life;
- Standard terminals, usage and Replacement easily;
- With ticking sound.

Ordering Information 订货说明

<u>WM FLL301</u>			
<u>-M</u>	<u>-12</u>	<u>-L</u>	
1	2	3	4
1 Part number 型号： WM FLL301		3 Rated Voltage(VDC)额定电压： 12: 12V； 24: 24V	
2Casw 外壳： M: Metal Bracket 带金属安装背；		4Case height 外壳高度： L: 39mm； D: 30mm	
Nil: No Bracket 没有安装背；			

Technical Characteristics 性能参数

Rated Voltage 额定电压	12VDC, 24VDC
Operating Voltage 工作电压	11VDC ~ 15VDC, 22VDC ~ 30VDC
Test Voltage 测试电压	13VDC ± 0.2VDC, 26VDC ± 0.4VDC
Test Temperature 测试温度	20°C ± 2°C
Switch Load 切换负载	0.1W ~ 150W
Max Power 最大负载	150W
Flashing Frequency 闪光频率	60 ~ 120 times per minute
Duty Ratio 占空比	30% ~ 70%
Operating Temperature 环境温度	-40°C ~ +80°C
Life 寿命	400 working hours
Weight 重量(Approx.)	25g

Layout (Bottom views, Unit: mm)外形尺寸、接线图 (底视图)

Dimensions (WM FLL301-D) 30.5×30.5×30	Dimensions(WM FLL301-L) 30.5×30.5×39

Dimensions (WM FLL301-D-M)	30.5×30.5×30(+14)	Dimensions (WM FLL301-L-M)	30.5×30.5×39(+14)
Wiring diagram(Bottom views)			